

DECLARATION OF PERFORMANCE N. CPR-GB1/0026

- 1) Unique identification code of the product-type: **ULTRAPLAN RENOVATION SCREED 3240**
- 2) Intended uses: **Cementitious screed material for internal use in floor construction**
- 3) Manufacturer: **MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD- www.mapei.co.uk**
- 4) Systems of AVCP: **System 4**
System 3 for reaction to fire
- 5) Harmonized standards: **EN 13813 :2002**

Notified bodies: **INSTYTUT TECHNIKI BUDOWLANEJ, N. 1488**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class A_{1f}
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C25
Flexural strength:	F5
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Peter Dube – Quality Manager**



Halesowen, 27/04/2022



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website.

<i>Revision 2 notes:</i>	<i>Revised Reaction to fire class from A_{2f}-s1 to A_{1f}</i>
--------------------------	--

ULTRAPLAN RENOVATION SCREED 3240
CE MARKING
Annex to DoP N. CPR-GB1/0026



 1488	 MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD www.mapei.co.uk
10 CPR-GB1/0026 EN 13813 EN13813 ULTRAPLAN RENOVATION SCREED 3240 ULTRAPLAN RENOVATION SCREED 3240 <i>Cementitious screed material for internal use in floor construction Cementitious screed material for internal use in floor construction</i>	
Reaction to fire:	Class A1fl
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C25
Flexural strength:	F5
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.